

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Pica INK Refill Set, black 55846 (APM 44/46)

Revision date: 22.11.2024

Page 1 of 16

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Pica INK Refill Set, black 55846

UFI: PXGN-3XDH-ESMX-TFDS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Industrial and professional use.

Sector of uses [SU] : Articles for printing and writing, Pens.

Uses advised against

Any non-intended use.

1.3. Details of the supplier of the safety data sheet

Company name: Pica-Marker GmbH

Street: Picastraße 5

Place: D-91356 Kirchhehrenbach

Telephone: +49 9191 320403-0

Telefax: +49 9191 320403-99

E-mail: info@pica-marker.com

Internet: www.pica-marker.com

1.4. Emergency telephone number:

Only from Malta: 112

Further Information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (amended by Regulation (EU) No 2020/878)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225

Repr. 1B; H360

Eye Dam. 1; H318

STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

propan-1-ol; n-propanol

C.I. Solvent Black 29

Signal word: Danger

Pictograms:



Hazard statements

H225

Highly flammable liquid and vapour.

H318

Causes serious eye damage.

H336

May cause drowsiness or dizziness.

H360

May damage fertility or the unborn child.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Pica INK Refill Set, black 55846 (APM 44/46)

Revision date: 22.11.2024

Page 2 of 16

Precautionary statements

- P201 Obtain special instructions before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P501 Dispose of contents/container to local/regional/national/international regulations.

Special labelling of certain mixtures

Restricted to professional users.

2.3. Other hazards

Endocrine disrupting properties: butanone; ethyl methyl ketone.

butanone; ethyl methyl ketone:

The substance is included in one of the lists of endocrine disruptors (list II, human).

In use, may form flammable/explosive vapour-air mixture.

The substances in the mixture (>0,1%) do not meet the PBT/vPvB criteria according to REACH, annex XIII.

This product does not contain a substance (> 0,1 %) that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
64-17-5	ethanol; ethyl alcohol			40 - < 45 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			
71-23-8	propan-1-ol; n-propanol			30 - < 35 %
	200-746-9	603-003-00-0	01-2119486761-29	
	Flam. Liq. 2, Eye Dam. 1, STOT SE 3; H225 H318 H336			
-	C.I. Solvent Black 29			10 - < 15 %
	938-781-3		01-2120081123-67	
	Repr. 1B; H360			
78-93-3	butanone; ethyl methyl ketone			< 1 %
	201-159-0	606-002-00-3		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64-17-5	200-578-6	ethanol; ethyl alcohol	40 - < 45 %
		inhalation: LC50 = 124,7 mg/l (vapours); oral: LD50 = >5000 mg/kg Eye Irrit. 2; H319: >= 50 - 100	



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Pica INK Refill Set, black 55846 (APM 44/46)

Revision date: 22.11.2024

Page 3 of 16

71-23-8	200-746-9	propan-1-ol; n-propanol	30 - < 35 %
		inhalation: LC50 = > 33,8 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = 8000 mg/kg	
-	938-781-3	C.I. Solvent Black 29	10 - < 15 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	

Further Information

butanone; ethyl methyl ketone: The substance is included in one of the lists of endocrine disruptors (list II; human).

Product does not contain listed SVHC substances > 0,1 % according to Regulation (EC) No. 1907/2006 Article 59 (REACH)

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Take off immediately all contaminated clothing.

First aider: Pay attention to self-protection!

After inhalation

Remove person to fresh air and keep comfortable for breathing. In case of respiratory tract irritation, consult a physician.

After contact with skin

Take off immediately all contaminated clothing. Wash with plenty of water. In case of skin irritation, seek medical treatment. Do not wash with: Solvents/Thinner

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

After ingestion

Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Do NOT induce vomiting. Never give anything by mouth to an unconscious person or a person with cramps. In all cases of doubt, or when symptoms persist, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

See sections 2 and 11

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂). Dry extinguishing powder. Extinguishing powder. Alcohol resistant foam.
In case of major fire and large quantities: Water spray

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Gas/vapours, irritant. Carbon monoxide (CO). Carbon dioxide (CO₂).

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes. Reignition possible over considerable distance.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Pica INK Refill Set, black 55846 (APM 44/46)

Revision date: 22.11.2024

Page 4 of 16

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Use water spray jet to protect personnel and to cool endangered containers.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Do not breathe gas/vapour/aerosol. Avoid contact with skin, eyes and clothes.

For non-emergency personnel

Remove persons to safety. Remove all sources of ignition. Ventilate affected area.

Wear personal protective equipment. (See section 8.)

For emergency responders

No special measures are necessary.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Danger of explosion! Cover drains. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Ventilate affected area.

Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Clean contaminated objects and areas thoroughly observing environmental regulations.

Other information

Clean with detergents. Avoid solvent cleaners.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation as well as local exhaust at critical locations.

Do not breathe gas/vapour/aerosol. Avoid contact with skin, eyes and clothes.

Wear suitable protective clothing. (See section 8.)

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges.

Flammable vapours can accumulate in head space of closed systems. In use, may form flammable/explosive vapour-air mixture. Heating causes rise in pressure with risk of bursting.

Advice on general occupational hygiene

The usual precautions for handling chemicals should be considered.

Keep away from food, drink and animal feedingstuffs.

Always close containers tightly after the removal of product. When using do not eat, drink or smoke. Wash hands before breaks and after work. Preventive skin protection with skin protection ointment. Take off contaminated clothing and wash it before reuse.

Further information on handling

General protection and hygiene measures: See section 8.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Pica INK Refill Set, black 55846 (APM 44/46)

Revision date: 22.11.2024

Page 5 of 16

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place. Protect against direct sunlight.

Ensure adequate ventilation of the storage area.

Make sure spills can be contained (e.g. sump pallets or kerbed areas).

Hints on joint storage

Do not store together with: Gas. Explosives. Oxidizing agents. Flammable solids. Pyrophoric liquids and solids.

Self-heating substances and mixtures. Substances and mixtures which, in contact with water, emit flammable gases.

Oxidizing liquids. Oxidizing solids. ammonium nitrate. Self-reactive substances and mixtures. Organic peroxides.

Non-combustible toxic substances. Radioactive substances. Infectious substances. Strong acid. Strong alkali.

Further information on storage conditions

Keep the packing dry and well sealed to prevent contamination and absorption of humidity.

Protect against: UV-radiation/sunlight. heat. Humidity frost.

storage temperature: 10 - 40°C

7.3. Specific end use(s)

See section 1.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limit values**

CAS No	Name of agent	ppm	mg/m ³	fib/cm ³	Category	Origin
78-93-3	Butanone	200	600		TWA (8 h)	
		300	900		STEL (15 min)	

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Pica INK Refill Set, black 55846 (APM 44/46)

Revision date: 22.11.2024

Page 6 of 16

DNEL/DMEL values

CAS No	Name of agent			
DNEL type	Exposure route		Effect	Value
64-17-5	ethanol; ethyl alcohol			
Worker DNEL, acute	inhalation		local	1900 mg/m ³
Worker DNEL, long-term	dermal		systemic	343 mg/kg bw/day
Worker DNEL, long-term	inhalation		systemic	950 mg/m ³
Consumer DNEL, acute	inhalation		local	950 mg/m ³
Consumer DNEL, long-term	dermal		systemic	206 mg/kg bw/day
Consumer DNEL, long-term	inhalation		systemic	114 mg/m ³
Consumer DNEL, long-term	oral		systemic	87 mg/kg bw/day
71-23-8	propan-1-ol; n-propanol			
Worker DNEL, long-term	inhalation		systemic	268 mg/m ³
Worker DNEL, acute	inhalation		systemic	1723 mg/m ³
Worker DNEL, long-term	dermal		systemic	136 mg/kg bw/day
Consumer DNEL, long-term	inhalation		systemic	80 mg/m ³
Consumer DNEL, acute	inhalation		systemic	1036 mg/m ³
Consumer DNEL, long-term	dermal		systemic	81 mg/kg bw/day
-	C.I. Solvent Black 29			
Worker DNEL, long-term	inhalation		systemic	0,94 mg/m ³
Worker DNEL, long-term	dermal		systemic	0,13 mg/kg bw/day
Consumer DNEL, long-term	inhalation		systemic	0,23 mg/m ³
Consumer DNEL, long-term	dermal		systemic	0,07 mg/kg bw/day
Consumer DNEL, long-term	oral		systemic	0,07 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Pica INK Refill Set, black 55846 (APM 44/46)

Revision date: 22.11.2024

Page 7 of 16

PNEC values

CAS No	Name of agent	
Environmental compartment		Value
64-17-5	ethanol; ethyl alcohol	
Freshwater		0,96 mg/l
Freshwater (intermittent releases)		2,75 mg/l
Marine water		0,79 mg/l
Marine water (intermittent releases)		2,75 mg/l
Freshwater sediment		3,6 mg/kg
Marine sediment		2,9 mg/kg
Secondary poisoning		0,72 mg/kg
Micro-organisms in sewage treatment plants (STP)		580 mg/l
Soil		0,63 mg/kg
71-23-8	propan-1-ol; n-propanol	
Freshwater		6,83 mg/l
Freshwater (intermittent releases)		10 mg/l
Marine water		0,683 mg/l
Freshwater sediment		27,5 mg/kg
Marine sediment		2,75 mg/kg
Micro-organisms in sewage treatment plants (STP)		96 mg/l
Soil		1,49 mg/kg

8.2. Exposure controls



Appropriate engineering controls

Use only in well-ventilated areas.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles, Wear safety glasses; chemical goggles (if splashing is possible).

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits.

In case of prolonged or frequently repeated skin contact: Wear suitable gloves.

Suitable material:

FKM (fluororubber). - Thickness of glove material: 0,4 mm

Breakthrough time \geq 8 h

Butyl rubber. - Thickness of glove material: 0,5 mm

Breakthrough time \geq 8 h

NBR (Nitrile rubber). - Thickness of glove material: 0,35 mm

Breakthrough time \geq 8 h

Use protective skin cream before handling the product.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The selected protective gloves have to satisfy the specifications of EU Directive EC/ 2016/425 and the



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Pica INK Refill Set, black 55846 (APM 44/46)

Revision date: 22.11.2024

Page 8 of 16

standard EN 374 derived from it.

Before using check leak tightness / impermeability. In the case of wanting to use the gloves again, clean them before taking off and air them well.

Skin protection

Wear fire/flamm resistant/retardant clothing. Wear anti-static footwear and clothing

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

Generation/formation of aerosols

Exceeding exposure limit values

Insufficient ventilation

Suitable respiratory protection apparatus: Combination filtering device (EN 14387) Type:: A/P1-3

Half-face mask or quarter facepiece: maximum use concentration for substances with exposure limits: P1 filter: up to a max. of 4 times the exposure limit. P2 filter: up to a max. of 10 times the exposure limit. P3 filter: up to a max. of 30 times the expo.

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Environmental exposure controls

Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	black
Odour:	characteristic
Odour threshold:	not determined
Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	78 °C
Flammability:	not determined
Lower explosion limits:	2,1 vol. %
Upper explosion limits:	15 vol. %
Flash point:	12 °C
Auto-ignition temperature:	340 °C
Decomposition temperature:	not relevant
pH-Value:	ca. 7
Viscosity / kinematic:	not determined
Water solubility:	easily soluble.
Solubility in other solvents	not determined
Dissolution rate:	not relevant
Partition coefficient n-octanol/water:	SECTION 12: Ecological information
Dispersion stability:	not relevant
Vapour pressure:	58 hPa
(at 20 °C)	
Density (at 20 °C):	0,861 g/cm ³
Bulk density:	not relevant
Relative vapour density:	not determined
Particle characteristics:	not relevant

9.2. Other information

Information with regard to physical hazard classes



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Pica INK Refill Set, black 55846 (APM 44/46)

Revision date: 22.11.2024

Page 9 of 16

Explosive properties

In use, may form flammable/explosive vapour-air mixture.

Sustained combustibility:

No sustained combustibility

Self-ignition temperature

Gas:

not determined

Oxidizing properties

none.

Other safety characteristics

Evaporation rate:

not determined

Solvent separation test:

not determined

Solvent content:

not determined

Solid content:

not determined

Sublimation point:

not relevant

Softening point:

not relevant

Pour point:

not relevant

Viscosity / dynamic:

not determined

Flow time:

not determined

Further Information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

Refer to section 10.5.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

In use may form flammable/explosive vapour-air mixture.

Heating causes rise in pressure with risk of bursting.

10.5. Incompatible materials

Materials to avoid: Oxidizing agents, strong. Strong acid. strong alkalis.

10.6. Hazardous decomposition products

In use, may form flammable/explosive vapour-air mixture. In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂). Nitrogen oxides (NO_x). carbon black.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

No data available.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Pica INK Refill Set, black 55846 (APM 44/46)

Revision date: 22.11.2024

Page 10 of 16

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64-17-5	ethanol; ethyl alcohol				
	oral	LD50 >5000 mg/kg	Rat	REACH Dossier	
	inhalation (4 h) vapour	LC50 124,7 mg/l	Rat	REACH Dossier	
71-23-8	propan-1-ol; n-propanol				
	oral	LD50 8000 mg/kg	Rat	REACH Dossier	OECD 401
	dermal	LD50 > 2000 mg/kg	Rabbit	REACH Dossier	OECD 402
	inhalation (4 h) vapour	LC50 > 33,8 mg/l	Rat	REACH Dossier	OECD 403
-	C.I. Solvent Black 29				
	oral	LD50 > 5000 mg/kg	Rat	REACH Dossier	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	REACH Dossier	OECD Guideline 402

Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye damage.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

May damage fertility or the unborn child. (C.I. Solvent Black 29)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Ethanol (CAS-No.: 64-17-5):

In-vitro mutagenicity: No experimental indications of mutagenicity in-vivo exist.

Reproductive toxicity: Exposure time: 18 weeks; Species: CD-1 Mouse. Method: OECD Guideline 416; Result:

NOAEL = 20700 mg/kg/day. Developmental toxicity/teratogenicity: Exposure time: 19d; Species: Sprague-Dawley

Rat. Method: OECD Guideline 414; Result: NOAEL = 16000 ppm (maternal toxicity), Result: NOAEL >= 20000 ppm (teratogenicity); Literature information: REACH Dossier

STOT-single exposure

May cause drowsiness or dizziness. (propan-1-ol; n-propanol)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Ethanol (CAS-No.: 64-17-5):

Subchronic oral toxicity: Exposure time: 90d; Species: Sprague-Dawley Rat. Method: OECD Guideline 408; Result: NOAEL = 1280 mg/kg; Literature information: REACH Dossier

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No data available.

11.2. Information on other hazards

Endocrine disrupting properties

Endocrine disrupting properties: butanone; ethyl methyl ketone.

The substance is included in one of the lists of endocrine disruptors (list II, human).

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Pica INK Refill Set, black 55846 (APM 44/46)

Revision date: 22.11.2024

Page 11 of 16

Other information

No data available.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64-17-5	ethanol; ethyl alcohol					
	Acute fish toxicity	LC50 14200 mg/l	96 h	Pimephales promelas	REACH Dossier	
	Acute algae toxicity	ErC50 275 mg/l	72 h	Chlorella vulgaris	REACH Dossier	
	Acute crustacea toxicity	EC50 5012 mg/l	48 h	Ceriodaphnia dubia	REACH Dossier	
	Crustacea toxicity	NOEC (9,6) mg/l	9 d	Daphnia magna	REACH Dossier	
71-23-8	propan-1-ol; n-propanol					
	Acute fish toxicity	LC50 4555 mg/l	96 h	Pimephales promelas	REACH Dossier	
	Acute algae toxicity	ErC50 9170 mg/l		Pseudokirchnerella subcapitata (48h)	REACH Dossier	
	Acute crustacea toxicity	EC50 1000 mg/l	48 h	Gammarus pulex	REACH Dossier	
	Crustacea toxicity	NOEC >100 mg/l	21 d	Daphnia magna	REACH Dossier	
-	C.I. Solvent Black 29					
	Acute fish toxicity	LC50 2 mg/l	96 h	Cyprinus carpio	REACH Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Desmodesmus subspicatus	REACH Dossier	OECD Guideline 201

12.2. Persistence and degradability

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
64-17-5	ethanol; ethyl alcohol			
	other guideline:	84%	20	REACH Dossier
	Biodegradable.			
71-23-8	propan-1-ol; n-propanol			
	-	75%	20	REACH Dossier
	Biodegradable.			
-	C.I. Solvent Black 29			
	OECD 301B / ISO 9439 / EEC 92/69 annex V, C.4-C	28	13	REACH Dossier
	Not easily bio-degradable (according to OECD-criteria).			

12.3. Bioaccumulative potential



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Pica INK Refill Set, black 55846 (APM 44/46)

Revision date: 22.11.2024

Page 12 of 16

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	ethanol; ethyl alcohol	-0,31
71-23-8	propan-1-ol; n-propanol	0,2
-	C.I. Solvent Black 29	< 0

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

The aforementioned statement applies to substances contained in the product with a minimum content of 0.1%.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

The aforementioned statement applies to substances contained in the product with a minimum content of 0.1%.

12.7. Other adverse effects

No data available.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. According to (EWC) European Waste Catalogue, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process. Control report for waste code/ waste marking according to (EWC) European Waste Catalogue:

List of Wastes Code - residues/unused products

160305 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; off-specification batches and unused products; organic wastes containing hazardous substances; hazardous waste

List of Wastes Code - used product

160305 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; off-specification batches and unused products; organic wastes containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1263

14.2. UN proper shipping name: PAINT

14.3. Transport hazard class(es): 3

14.4. Packing group: II

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Pica INK Refill Set, black 55846 (APM 44/46)

Revision date: 22.11.2024

Page 13 of 16

Hazard label:

3



Classification code:

F1

Special Provisions:

163 367 640D 650

Limited quantity:

5 L

Excepted quantity:

E2

Transport category:

2

Hazard No:

33

Tunnel restriction code:

D/E

Inland waterways transport (ADN)

14.1. UN number or ID number:

UN 1263

14.2. UN proper shipping name:

Paint

14.3. Transport hazard class(es):

3

14.4. Packing group:

II

Hazard label:

3



Classification code:

F1

Special Provisions:

163 367 640D 650

Limited quantity:

5 L

Excepted quantity:

E2

Marine transport (IMDG)

14.1. UN number or ID number:

UN 1263

14.2. UN proper shipping name:

PAINT

14.3. Transport hazard class(es):

3

14.4. Packing group:

II

Hazard label:

3



Marine pollutant:

NO

Special Provisions:

163 367

Limited quantity:

5 L

Excepted quantity:

E2

EmS:

F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:

UN 1263

14.2. UN proper shipping name:

PAINT

14.3. Transport hazard class(es):

3

14.4. Packing group:

II

Hazard label:

3



Special Provisions:

A3 A72 A192

Limited quantity Passenger:

1 L

Passenger LQ:

Y341

Excepted quantity:

E2



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Pica INK Refill Set, black 55846 (APM 44/46)

Revision date: 22.11.2024

Page 14 of 16

IATA-packing instructions - Passenger:	353
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	364
IATA-max. quantity - Cargo:	60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

See section 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2010/75/EU on industrial emissions: 72,14 % (External SDS)

Directive 2004/42/EC on VOC in paints and varnishes: 72,14 % (External SDS)

Information according to Directive 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (amended by Regulation (EU) No 2020/878)

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

REACH 1907/2006 Appendix XVII, No (mixture): 3, 40

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

ethanol; ethyl alcohol

propan-1-ol; n-propanol

C.I. Solvent Black 29

SECTION 16: Other information

Changes

Rev. 1,0; Initial release: 25.11.2024



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Pica INK Refill Set, black 55846 (APM 44/46)

Revision date: 22.11.2024

Page 15 of 16

Abbreviations and acronyms

Flam. Liq: Flammable liquid
Eye Dam: Eye damage
Eye Irrit: Eye irritation
Repr: Reproductive toxicity
STOT SE: Specific target organ toxicity - single exposure
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
CAS: Chemical Abstracts Service
CLP: Classification, Labelling and Packaging of substances and mixtures
DNEL: Derived No Effect Level
d: day(s)
EINECS: European INventory of Existing Commercial chemical Substances
ELINCS: European List of Notified Chemical Substances
ECHA: European Chemicals Agency
EWC: European Waste Catalogue
IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organization
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)
h: hour
LOAEL: Lowest observed adverse effect level
LOAEC: Lowest observed adverse effect concentration
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
NOAEL: No observed adverse effect level
NOAEC: No observed adverse effect concentration
NLP: No-Longer Polymers
N/A: not applicable
OECD: Organisation for Economic Co-operation and Development
PNEC: predicted no effect concentration
PBT: Persistent bioaccumulative toxic
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
REACH: Registration, Evaluation, Authorisation of Chemicals
SVHC: substance of very high concern
TRGS: Technische Regeln für Gefahrstoffe
UN: United Nations
VOC: Volatile Organic Compounds
WGK: Water Hazard Class (Germany)

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Repr. 1B; H360	Calculation method
Eye Dam. 1; H318	Calculation method
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Pica INK Refill Set, black 55846 (APM 44/46)

Revision date: 22.11.2024

Page 16 of 16

H336	May cause drowsiness or dizziness.
H360	May damage fertility or the unborn child.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)